



SW Sustainability Solutions Inc.






TrueForm®

NITRILE EXAMINATION GLOVES

TF-95NV (2,000 PER CASE, 200 PER BOX)

- ECOTEK SUSTAINABLE TECHNOLOGY
- LOW DERMATITIS POTENTIAL (LDP)

TF					TF-95NV
WEIGHT	LENGTH	THICKNESS	FEATURES	COLOR	EcoTek
 3.8g (large size)	 9.5"	 3.5 mil 2.4 mil	EcoTek®	ROYAL BLUE	

VALUE AND PERFORMANCE HAND PROTECTION FOR HEALTHCARE FACILITIES

- EcoTek® Sustainable Technology reduces landfill waste by 92.6% in only 2.5 years. ¹
- EcoTek® Sustainable Technology reduces the release of greenhouse gas emissions during incineration ² (ie. Sulfur Dioxide, SO₂ ↓ 82%).
- Low Dermatitis Potential (LDP) is an FDA approved claim that gloves were clinically tested and have a reduced potential to cause skin irritation. ³
- Tested for use with chemotherapy drugs and chemical permeation using ASTM D6978 Assessment of Resistance of Medical Gloves to Permeation by Chemotherapy Drugs. Breakthrough time (BTT) >240 minutes.
- Flat Stacked Dispensing reduces glove waste by 10-20%.

Finger textured surface for wet and dry grip

Optimal thickness for durability and tactile sensitivity

Tear-resistant beaded cuff for easy donning



SW®
Visit our website swssglobal.com

Trademarks and registered trademarks are the property of SW and its affiliates.
©2025 SW. All rights reserved.



WOMEN OWNED™



TECHNICAL DATA



TF-95NV (2,000 PER CASE, 200 PER BOX)

- ECOTEK SUSTAINABLE TECHNOLOGY
- LOW DERMATITIS POTENTIAL (LDP)

PRODUCT DESCRIPTION

SPECIFICATIONS

PRODUCT	TrueForm®
GRADE	Powder-Free Exam
MATERIAL	Nitrile
THICKNESS FINGER	3.5mil 0.08mm
PALM	2.4mil 0.06mm
COLOR	Navy
SURFACE OUTER	Finger Textured
INNER	Low Dermatitis Potential (LDP)
LENGTH	9.5" 242mm
WEIGHT	3.5g
FIT TYPE	Ambidextrous
CUFF TYPE	Beaded
WATERTIGHT AQL	1.5

PHYSICAL PROPERTIES

	PRE-AGING	POST-AGING
TENSILE STRENGTH:	≥14 MPA	≥14 MPA
ELONGATION:	≥500%	≥400%

INTEGRATED TECHNOLOGIES

ECOTEK Sustainable Technology: Reduces landfill waste by 92.6% in only 2.5 years. ¹

ECOTEK Sustainable Technology: Reduces greenhouse gas emissions when incinerated. ²

Low Dermatitis Potential (LDP): FDA approved claim reduces potential for skin irritation.

Chemotherapy Drugs and Chemical Permeation: Provides safe handling of hazardous drugs.

100% Air Inspected



* Specifications based on size Medium glove

STANDARDS & CERTIFICATIONS



Please visit [swsglobal.com/symbols](https://www.swsglobal.com/symbols) for information on standards used on this document.



ORDERING

ITEM NO.	SIZE	PALM WIDTH	PACKAGING
N191341	XS 5½ – 6	3.0" 75mm	200 gloves/box, 10 boxes/case, 2000 gloves/case
N191342	S 6½ – 7	3.3" 85mm	200 gloves/box, 10 boxes/case, 2000 gloves/case
N191343	M 7½ – 8	3.7" 95mm	200 gloves/box, 10 boxes/case, 2000 gloves/case
N191344	L 8½ – 9	4.1" 105mm	200 gloves/box, 10 boxes/case, 2000 gloves/case
N191345	XL 9½ – 10	4.5" 115mm	200 gloves/box, 10 boxes/case, 2000 gloves/case
N191346	2XL 10½ – 11	4.9" 125mm	200 gloves/box, 10 boxes/case, 2000 gloves/case

References

¹ EcoTek gloves tested to ASTM D5526-12 Standard Test Method for Determining Anaerobic Biodegradation of Plastic Materials Under Accelerated Landfill Conditions. Results are 92.6% biodegradation in 60% solids landfill at 945 days. Future results cannot be predicted/ extrapolated.

² Ecotek Incineration - Results are based on third-party testing comparing emissions to a standard nitrile glove, incinerated in a dual-chamber incinerator.

³ LDP – Skin Sensitization Test (Modified Draize-95 Test), CPT Testing Company, 1/26/2021.

Keep out of sunlight. Store in a cool, dry place.
Keep away from sources of ozone or ignition.



R_N191340525



SW®
Contact us today +1.510.429.8692

Trademarks and registered trademarks are the property of SW and its affiliates.
©2025 SW. All rights reserved.

