



FEEL THE SW
DIFFERENCE®

DESIGNED TO ENHANCE WORKER PERFORMANCE.



PowerForm®

PF-12OR

POWDER-FREE NITRILE EXTENDED-CUFF
EXAMINATION GLOVES WITH SUSTAINABLE
ECOTEK TECHNOLOGY

**DESIGNED FOR FOOD SAFETY, THESE DURABLE
GLOVES HELP PREVENT CONTAMINATION
WHILE PROVIDING EXCEPTIONAL GRIP AND
DEXTERITY IN DEMANDING TASKS**

- EcoTek Sustainable Technology – Engineered for high performance while reducing landfill waste by 92.6% over 2.5 years and minimizing toxic emissions during incineration.*
- Clean Washed & 100% Air Inspected – Ensures gloves are free from residues and contaminants.
- Silicone-Free – Eliminates risk of contamination in sensitive food and industrial processes.
- FDA-Compliant – These gloves have passed rigorous testing for total extractives, meeting the stringent standards set by the US FDA 21 CFR 177.2600 for materials in contact with food. Safe for extended contact with wet and oily foods.
- Exceeds 1.5 AQL Standards – Provides consistent reliability and reduced risk of defects.
- Comfortable Ergonomic Fit – Designed for all-day wear with excellent dexterity and tactile sensitivity.
- Durability & Superior Grip – Built for strength with a fish scale texture that delivers superior grip in dry, wet, and oily conditions.

PF

PF-12OR

WEIGHT	LENGTH	THICKNESS	FEATURES	COLOR	ECOTEK
13.3g (large size)	12.0"	11.2 mil 8.0 mil	EcoTek® Clean Washed Air Inspected	ORANGE	ECOTEK



**25% MORE
GRIP
PERFORMANCE**

Compared to regular market products (ANSI/
ISEA 105 Abrasion Level 03)*

**25% HIGHER
PUNCTURE
IMPACT
RESISTANCE**

Compared to regular market pattern*

**30% GREATER
ABRASIVE
PERFORMANCE**

Compared to conventional nitrile gloves
(minimum puncture >2000g)*



Feel the
difference.™

SW®
33278 Central Avenue, Unit 102, Union City, CA 94587, USA
Tel: +1.510.429.8692 | Fax: +1.510.487.5347

Trademarks and registered trademarks are the property of SW and its affiliates.
©2025 SW. All rights reserved.



WOMEN
OWNED



* The performance evaluations presented are based on laboratory testing conducted according to global standards. Actual performance may vary depending on real-world application conditions.

TECHNICAL DATA



PF-12OR

POWDER-FREE NITRILE EXTENDED-CUFF EXAMINATION GLOVES
WITH SUSTAINABLE ECOTEK TECHNOLOGY

POLYCARBIN

THIS GLOVE IS RECYCLABLE THROUGH
POLYCARBIN'S LAB RECYCLING PROGRAM.

REQUEST A SAMPLE
AND EXPERIENCE THE
DIFFERENCE.



PRODUCT DESCRIPTION

SPECIFICATIONS

PRODUCT	PowerForm®
GRADE	Powder-Free Exam
MATERIAL	Nitrile
THICKNESS	FINGER 11.2mil 0.28mm
	PALM 8.0mil 0.20mm
	CUFF 5.6mil 0.14mm
COLOR	Orange
SURFACE	Fully Textured
LENGTH	12.0" 290mm
WEIGHT	13.3g
FIT TYPE	Ambidextrous
CUFF TYPE	Beaded
WATERTIGHT AQL	1.5
ORIGIN COUNTRY	Sri Lanka

PHYSICAL PROPERTIES

	PRE-AGING	POST-AGING
TENSILE STRENGTH:	14 MPa	14 MPa
ELONGATION:	500%	400%

INTEGRATED TECHNOLOGIES

ECOTEK Sustainable Technology: Product has
been tested per ASTM D5526*

100% Air Inspected

Clean Washed



* Specifications based on size Large glove

STANDARDS & CERTIFICATIONS

EN ISO 21420:2020
EN 455-2000-2015
ASTM D6978-05 (2019)
Reach EU 1907/2006
EU 2016/425
FDA 21 CFR 177.2600

EN ISO 374-5:2016



Please visit swssglobal.com/symbols for information on standards used on this document.

ORDERING

ITEM NO.	SIZE	PALM WIDTH	PACKAGING
N909753	M 7½ – 8	3.7" 95mm	50 gloves per box 10 boxes per case
N909754	L 8½ – 9	4.0" 104mm	50 gloves per box 10 boxes per case
N909755	XL 9½ – 10	4.4" 112mm	50 gloves per box 10 boxes per case
N909756	2XL 10½ – 11	4.8" 122mm	50 gloves per box 10 boxes per case
N909757	3XL 11½ – 12	5.2" 132mm	50 gloves per box 10 boxes per case

APPLICATIONS

Food Handling
Food Processing
Industrial Tasks

Keep out of sunlight. Store in a cool, dry place.
Keep away from sources of ozone or ignition.



10°C / 30°C

R_N90975X1125



SW®
33278 Central Avenue, Unit 102, Union City, CA 94587, USA
Tel: +1.510.429.8692 | Fax: +1.510.487.5347
Trademarks and registered trademarks are the property of SW and its affiliates.
©2025 SW. All rights reserved.



* Validated by a third-party private lab, EcoTek gloves achieved 92.6% landfill waste reduction over 2.5 years under conditions that simulate modern landfills. Future results cannot be predicted. For more information on the test reports, contact cs@swssglobal.com.